



Spijkstaal

SPIJKSTAAL 301

The Spijkstaal 301 is designed for the easy movement of loads up to 3,000 kg. This vehicle offers a reliable solution for sectors where manual transport is traditionally required. With its powerful electric motor and compact design, the vehicle provides an environmentally friendly and cost-effective option for business logistics.

[SPIJKSTAAL.COM](https://www.spijkstaal.com)

301

DRIVE/BATTERY	301	301L	301LZ	
Asynchrone AC motor	2.3	2.3	2.3	kW
Battery voltage	24	24	24	V
Battery capacity	270	270	270	Ah
Transmission	1:11	1:11	1:25	

PERFORMANCE

Max. speed	13	13	9	km/h
Pull capacity	1.000	1.500	3.000	kg
Max. drawbar pull	1.200	1.200	1.750	N

WEIGHTS

Service weight (incl. batt.)	470	470	470	kg
------------------------------	-----	-----	-----	----

DIMENSIONS

Lenght	1.095	1.265	1.265	mm
Width	750	750	750	mm
Track width rear	668	635	635	mm
Wheelbase	675	950	950	mm
Ground clearance, center of wheelbase	70	40	40	mm
Turning radius	975	1.250	1.250	mm

TYRES/SUSPENSION

Tyre size, front	300*75	300*75	300*75
Tyre size, rear	180*50(2)	200*50(4)	200*50(4)
Suspension front	Rigid	Rigid	Rigid

BRAKES

Service brake	Electromagnetic brake
Parking brake	Electromagnetic brake

OPTIONS E.G.

Battery exchange system	Bluespot
Flash light	Various trailer couplings



Scan and view this vehicle online