



***Spijkstaal***

## **SPIJKSTAAL 306-308**

The Spijkstaal 306 and 308 have towing capacities of 6,000 kg and 8,000 kg respectively, making them suitable for a wide range of transport tasks, even on different surfaces and slopes. These vehicles are widely used in the aviation, defense, industrial sectors, and healthcare institutions. Thanks to the extra-low step and ergonomically placed seat at hip height, the tugs offer a high level of user convenience.

**[SPIJKSTAAL.COM](https://spijkstaal.com)**

# 306-308

DRIVE/BATTERY	306	308	
Asynchrone AC motor	5	10	kW
Battery voltage	24	48	V
Battery capacity	480	320	Ah
Transmission	1:19	1:19	

PERFORMANCE			
Max. speed	16	16	km/h
Pull capacity	6.000	8.000	kg
Max. drawbar pull	5.100	7.000	N

WEIGHTS			
Service weight (incl. batt.)	1.095	1.095	kg

DIMENSIONS			
Lenght	2.106	2.106	mm
Width	1.000	1.000	mm
Height (with cabin)	1.810	1.810	mm
Track width rear	840	840	mm
Wheelbase	1.480	1.480	mm
Ground clearance, center of wheelbase	100	100	mm
Turning radius	2.105	2.105	mm

TYRES/SUSPENSION			
Tyre size, front	5.00*8	5.00*8	
Tyre size, rear	5.00*8	5.00*8	
Suspension front & rear	Helical spring with shock absorber		

BRAKES	
Service brake	Hydraulic operated disc brake
Parking brake	Electromagnetic brake

OPTIONS E.G.		
Pneumatic tyres	Bluespot	Cabin
Flash light	Various trailer couplings	



Scan and view this vehicle online